



## AMS CL

- Available for viscous liquids.
- Available with compressed air supply.
- Constant feeding.
- Level control.
- Stroke speed (freq.) adjustment 0-100%.
- Stroke length adjustment.



Self Venting

Viscous Liquids

Compressed Air

Accessories

| FLOW |                  |                     | Delivery Hose<br>(PVDF) | Suction Ho |
|------|------------------|---------------------|-------------------------|------------|
| 2505 | 5 l/h at 25 bar  | 1,32 GPH at 362 PSI | 4 x 6                   | 4 x 6      |
| 1510 | 10 l/h at 15 bar | 2,64 GPH at 217 PSI | 4 x 6                   | 4 x 6      |
| 1015 | 15 l/h at 10 bar | 3,96 GPH at 145 PSI | 6 x 8                   | 6 x 8      |
| 0720 | 20 l/h at 7 bar  | 5,28 GPH at 101 PSI | 6 x 8                   | 6 x 8      |
| 0340 | 40 l/h at 3 bar  | 10,56 GPH at 43 PSI | 8 x 10                  | 8 x 12     |
| 0260 | 60 l/h at 2 bar  | 15,85 GPH at 29 PSI | 8 x 10                  | 8 x 12     |

## CONTACTS

EMEC srl

Via Donatori di Sangue, 1  
02100 Vazia (RI) ITALY

Tel. +39 - 07462284 1

Tel. +39 - 07461725114

Fax +39 - 07462284 2

email: [info@emec.it](mailto:info@emec.it)

## WORLDWIDE

- # Benelux
- # Brazil
- # China
- # France
- # Germany
- # Russia
- # Taiwan
- # United Kingdom

## IQ&amp;ISO CERTIFICATIONS



ISO 9001:2008  
ISO 14001:2004  
OHSAS 18001:2007

EMEC srl 2012 - \*PIVA 00620840579